

PO Box 2317 Jacksonville FL 32203-9956 SDS Communication for your recent order



658 2 SP 0.480 E0026X I0198 D2069599778 S2 P3734016 0001:0006

# - Որժրժրդը[ՍլթվՍՍ-|Սլի][լի][լի-|Սլի-Աժվի-Ժիոժիլդեկ[լդ։



12/08/16

Enclosed, please find Safety Data Sheets for your recent orders: 5404460 You can find a complete library of more than 11,000 data sheets at our web site www.supplyworks.com If you have any questions, please contact Customer Service at 866-412-6726

482915 00001

## (REN05002-AM / 880257)

<u>Version 1.0</u> Revision Date 04/29/2015 Print Date 05/28/2015

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : Renown® Heavy Duty Glass Cleaner

Material number : A00124

Manufacturer or supplier's details

Company : Interline Brands

Address : 701 San Marco Blvd.

Jacksonville, FL 32207

Telephone : 1-866-412-6726

Emergency telephone numbers				
For SDS Information	: 1-866-412-6726			
For a Medical Emergency	: 1-800-424-9300			
For a Transportation Emergency	: Chemtrec 1-800-424-9300			

Note: Products labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations: The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	colourless, clear
Odour	like fruit

**GHS Classification** 

Gases under pressure

: Liquefied gas

**GHS Label element** 

Hazard pictograms

 $\Diamond$ 

Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.

Precautionary statements : Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F. P403 Store in a well-ventilated place.

## **Potential Health Effects**

## (REN05002-AM / 880257)

 Version 1.0
 Revision Date 04/29/2015
 Print Date 05/28/2015

Carcinogenicity:

**OSHA** 

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

ethanol

64-17-5

2-butoxyethanol 111-76-2

No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

equal to 0.1% is identified as a carcinogen or pote

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous components**

Chemical Name	CAS-No.	Concentration [%]	
propane	74-98-6	>= 1 - < 5	
ethanol	64-17-5	>= 1 - < 5	
butane	106-97-8	>= 1 - < 5	
2-butoxyethanol	111-76-2	>= 1 - < 5	

## **SECTION 4. FIRST AID MEASURES**

General advice : Do not leave the victim unattended.

Get medical attention immediately if symptoms occur. Show this safety data sheet to the doctor in attendance.

If inhaled : If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Rinse thoroughly with plenty of water for at least 15 minutes

and consult a physician.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Keep respiratory tract clear.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

#### **SECTION 5. FIREFIGHTING MEASURES**

## (REN05002-AM / 880257)

Version 1.0		Revision Date 04/29/2015	Print Date 05/28/2015
Suitable extinguishing media	:	Dry chemical Carbon dioxide (CO2) Foam	
Unsuitable extinguishing media	:	High volume water jet	
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to courses.	enter drains or water
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Smoke	
Specific extinguishing methods	:	Use extinguishing measures that are ap circumstances and the surrounding env	
Further information	:	Standard procedure for chemical fires. Collect contaminated fire extinguishing must not be discharged into drains. Fire residues and contaminated fire exti be disposed of in accordance with local	inguishing water must
Special protective equipment for firefighters	:	Wear self-contained breathing apparatu necessary.	s for firefighting if

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures Use personal protective equipment.
 Ensure adequate ventilation.
 Remove all sources of ignition.
 Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal. Neutralise with acid.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling

: Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

(REN05002-AM / 880257)

 Version 1.0
 Revision Date 04/29/2015
 Print Date 05/28/2015

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Oxidizing agents

Do not freeze.

Storage temperature : < 49 °C

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
ethanol	64-17-5	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0

#### **Biological occupational exposure limits**

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-BUTOXYETHANOL	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after	200 mg/g	ACGIH BEI

# (REN05002-AM / 880257)

Version 1.0		R	Revision Date 04/29/2015			Print Date 05/28/2015		
L		1	1	1	ceases)	1		
Remarks:	Creatinine							

Personal protective equipment

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection

Remarks

: The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection

: Eye wash bottle with pure water

Safety glasses Face-shield

Skin and body protection

: impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance** 

: Aerosol containing a liquefied gas

Colour

: colourless, clear

Odour

like fruit

Odour Threshold

: no data available

pΗ

10 - 11

Melting point/freezing point

: not applicable

**Boiling point** 

: no data available

Flash point

Evaporation rate

not applicable

: no data available

Flammability (solid, gas)

: The product is not flammable.

Upper explosion limit Lower explosion limit : no data available : no data available

Vapour pressure

no data available

Relative vapour density

: no data available

Density

: 0.993 g/cm3

Solubility(ies)

Water solubility

: completely soluble

# (REN05002-AM / 880257)

Version 1.0

Revision Date 04/29/2015

Print Date 05/28/2015

Partition coefficient: n-

octanol/water

: no data available

Auto-ignition temperature

: not determined

Thermal decomposition

: no data available

Heat of combustion

: 3.07 kJ/g

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity

: Stable

Chemical stability

: Stable under normal conditions.

Possibility of hazardous reactions

: Vapours may form explosive mixture with air.

Conditions to avoid

: Heat, flames and sparks.

Incompatible materials

: Oxidizing agents

Hazardous decomposition

products

Carbon dioxide (CO2)
Carbon monoxide

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Acute toxicity**

#### **Product:**

Acute oral toxicity

: Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity

; Acute toxicity estimate : > 10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity

: Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

#### **Components:**

propane:

Acute inhalation toxicity

LC50 mouse: 1,237 mg/l

Exposure time: 2 h

LC50 rat: 658 mg/l Exposure time: 4 h

LC50 rat: 1,355 mg/l



## (REN05002-AM / 880257)

Version 1.0

Revision Date 04/29/2015

Print Date 05/28/2015

ethanol:

Acute oral toxicity

: LD50 Oral rat: 7,060 mg/kg

Acute inhalation toxicity

: LC50 rat: 124.7 mg/l Exposure time: 4 h

butane:

Acute inhalation toxicity

; LC50 mouse: 1,237 mg/l

Exposure time: 2 h

LC50 rat: 1,355 mg/l

#### Skin corrosion/irritation

**Product:** 

Remarks: May cause skin irritation and/or dermatitis.

#### Serious eye damage/eye irritation

**Product:** 

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

## Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

## Reproductive toxicity

no data available

propane:

ethanol:

butane:

2-butoxyethanol:

## STOT - single exposure

no data available

STOT - repeated exposure

no data available

**Aspiration toxicity** 

no data available

#### **Further information**

**Product:** 

Remarks: no data available

# (REN05002-AM / 880257)

Version 1.0

Revision Date 04/29/2015

: Remarks: no data available

Print Date 05/28/2015

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

no data available

#### Persistence and degradability

no data available

#### **Bioaccumulative potential**

**Product:** 

Partition coefficient: n-

octanol/water Components:

butane:

Partition coefficient: n-

octanol/water

: Pow: 2.89

Mobility in soil

no data available

#### Other adverse effects

no data available

**Product:** 

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

**Substances** 

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: no data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues

: Dispose of in accordance with local regulations.

Contaminated packaging

Empty remaining contents.
 Dispose of as unused product.
 Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

UN1950, Aerosols, 2.2,



(REN05002-AM / 880257)

Version 1.0	Revision Date 04/29/2015	Print Date 05/28/2015
Transportation Regulation UN1950, AEROSOLS, 2.2		
Transportation Regulation UN1950, Aerosols, non-fla		
Transportation Regulation UN1950, Aerosols, non-fla		
Transportation Regulation UN1950, AEROSOLS, 2.2		

#### **SECTION 15. REGULATORY INFORMATION**

#### **EPCRA - Emergency Planning and Community Right-to-Know Act**

## **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
2,2'-iminodiethanol	111-42-2	100	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Sudden Release of Pressure Hazard

SARA 302 : SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 : SARA 313: This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

California Prop 65 WARNING! This product contains a chemical known to the

State of California to cause cancer.

2,2'-iminodiethanol 111-42-2

## The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

DSL This product contains one or several components that are not on the

Canadian DSL nor NDSL.

AICS Not in compliance with the inventory

NZICS
Not in compliance with the inventory
PICCS
Not in compliance with the inventory
Not in compliance with the inventory
Not in compliance with the inventory

#### Inventory Acronym and Validity Area Legend:

## SAFETY DATA SHEET

# Renown® Heavy Duty Glass Cleaner

(REN05002-AM / 880257)

Version 1.0

Revision Date 04/29/2015


Print Date 05/28/2015

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

#### SECTION 16. OTHER INFORMATION

#### **Further information**

NFPA:



Special hazard.

## HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

#### OSHA GHS Label Information:

Hazard pictograms



Signal word Hazard statements Precautionary statements : Warning:

Contains gas under pressure; may explode if heated.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.





(REN05002-AM / 880257)

Version 1.0

Revision Date 04/29/2015

Print Date 05/28/2015

1000815