SAFETY DATA SHEET



1. Identification				
Product number	1000010459			
Product identifier	Vandalism Mark & Stain Remover			
Company information	Claire Manufacturing Co. 1005 S. Westgate Drive Addison, IL 60101 United States			
Company phone	General Assistance 1-630-543-7600			
Emergency telephone US	1-866-836-8855			
Emergency telephone outside US	1-952-852-4646			
Version #	01			
Recommended use	Cleaner			
Recommended restrictions	None known.			
2. Hazard(s) identification				
Physical hazards	Flammable aerosols	Category 1		
Health hazards	Skin corrosion/irritation	Category 2		
	Germ cell mutagenicity	Category 1		
	Carcinogenicity	Category 1		
	Reproductive toxicity	Category 2		
	Specific target organ toxicity, repeated exposure	Category 2		
	Aspiration hazard	Category 1		
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2		
	Hazardous to the aquatic environment, long-term hazard	Category 2		
OSHA defined hazards	Not classified.			
Label elements				
Signal word	Danger			
Hazard statement	Extremely flammable aerosol. May be fatal if s May cause genetic defects. May cause cance child. May cause damage to organs through p	swallowed and enters airways. Causes skin irritation. r. Suspected of damaging fertility or the unborn rolonged or repeated exposure.		
Precautionary statement				

Obtain special instructions before use. Do not handle until all safety precautions have been read Prevention and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed; Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If Response exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Storage Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal Hazard(s) not otherwise None known. classified (HNOC)

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Methylene Chloride		75-09-2	40 - 60
Butane		106-97-8	20 - 40
Perchloroethylene		127-18-4	10 - 20
Toluene		108-88-3	10 - 20
Propane		74-98-6	2.5 - 10
Cocoyl Diethanolamide		68603-42-9	1 - 2.5
Diethanolamine		111-42-2	0.1 - 1
Propylene Oxide		75-56-9	0.1 - 1
Other components below reportable levels			0.1 - 1

Other components below reportable levels

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Dizziness. Headache. Nausea. Irritation of eyes and mucous membranes. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.
5. Fire-fighting measures	
Suitable extinguishing media	Powder. Foam. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment	Firefighters must use standard protective equipment including flame retardant coat, helmet with

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. and precautions for firefighters

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose equipment/instructions holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

> Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Fire-fighting

Specific methods

Personal precautions, Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe protective equipment and gas. Do not touch damaged containers or spilled material unless wearing appropriate protective emergency procedures clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flarnes in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 1 Aerosol.
including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Components	Туре	Value	
Methylene Chloride (CAS 75-09-2)	STEL	125 ppm	
,	TWA	25 ppm	
US. OSHA Table Z-1 Limits for Air	r Contaminants (29 CFR 1910.1	000)	
Components	Туре	Value	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
Propylene Oxide (CAS 75-56-9)	PEL	240 mg/m3	
,		100 ppm	
US. OSHA Table Z-2 (29 CFR 1910	0.1000)		
Components	Туре	Value	
Perchloroethylene (CAS 127-18-4)	Ceiling	200 ppm	
	TWA	100 ppm	
Toluene (CAS 108-88-3)	Ceiling	300 ppm	
	TWA	200 ppm	
US. ACGIH Threshold Limit Value	S		
Components	Туре	Value	Form
Butane (CAS 106-97-8)	STEL	1000 ppm	···· · ·
Diethanolamine (CAS 111-42-2)	TWA	1 mg/m3	Inhalable fraction and vapor.
Methylene Chloride (CAS 75-09-2)	TWA	50 ppm	
Perchloroethylene (CAS 127-18-4)	STEL	100 ppm	
-	TWA	25 ppm	
Propylene Oxide (CAS 75-56-9)	TWA	2 ppm	

US. ACGIH Threshold Lin Components	nit Values Type		Va	alue	Form
Toluene (CAS 108-88-3)	TWA		20) ppm	
US. NIOSH: Pocket Guide	to Chemical Hazards				
Components	Туре		Va	alue	
Butane (CAS 106-97-8)	TWA			900 mg/m3 90 ppm	
Diethanolamine (CAS 111-42-2)	TWA		15	5 mg/m3	
Propane (CAS 74-98-6)	TWA		18	ppm 300 mg/m3)00 ppm	
Toluene (CAS 108-88-3)	STEL		56	60 mg/m3 50 ppm	
	TWA		37	75 mg/m3 10 ppm	
Biological limit values ACGIH Biological Exposu					
Components	Value	Determinant	Specimen	Sampling Ti	me
Methylene Chloride (CAS 75-09-2)	0.3 mg/l	Dichlorometha ne	Urine	*	
Perchloroethylene (CAS 127-18-4)	0.5 mg/l	Tetrachloroethy lene	Blood	*	
	3 ppm	Tetrachloroethy lene	End-exhaled air		
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*	
	0.03 mg/l 0.02 mg/l	Toluene Toluene	Urine Blood	*	
* - For sampling details, ple	•		Diood		
Exposure guidelines					
US - California OELs: Ski	n designation				
Diethanolamine (CAS Toluene (CAS 108-88-	Can be	Can be absorbed through the skin. Can be absorbed through the skin. es			
Perchloroethylene (CA	US - Minnesota Haz Subs: Skin designation applies Perchloroethylene (CAS 127-18-4) Toluene (CAS 108-88-3)			2 5. 25.	
US ACGIH Threshold Lim	-	tion			
Diethanolamine (CAS	•		absorbed throu	•	
Appropriate engineering controls	should be matched t or other engineering	o conditions. If app controls to maintain not been establish	licable, use pro n airborne leve ed, maintain ai	cess enclosures Is below recomm rborne levels to	used. Ventilation rates s, local exhaust ventilation, nended exposure limits. If an acceptable level. Eye g this product.
Individual protection measure Eye/face protection	s, such as personal pro Wear safety glasses	• •			
Hand protection	Wear appropriate ch	emical resistant gio	wes.		
Skin protection					¹
Other	wear appropriate ch	emical resistant cio	thing. Use of a	n impervious ap	ron is recommended.
Skin protection					
Respiratory protection	If permissible levels air-supplied respirate		NOSH mechar	nical filter / orgar	lic vapor cartridge or an
Thermal hazards	Wear appropriate the	ermal protective clo	thing, when ne	cessary.	
General hygiene considerations	When using, do not a as washing after han wash work clothing a	dling the material a	ind before eatir	ng, drinking, and	al hygiene measures, such /or smoking. Routinely

9. Physical and chemical	properties
Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	87 °F (30.55 °C) estimated
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	40 - 55 psig @20C estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific gravity	0.473 estimated
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	Hydrogen chloride.
11. Toxicological informat	ion
Information on likely routes of e	xposure
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Dizziness. Headache. Nausea. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Irritation of eyes and mucous membranes. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and en	
Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Diethanolamine (CAS 111-4	2-2)	
Acute		
Oral		
LD50	Rat	1100 mg/kg
Methylene Chloride (CAS 75	5-09-2)	
Acute		
Dermal	5.4	
LD50	Rat	> 2000 mg/kg, Days
Inhalation	Maura	
LC50	Mouse	49 mg/l, 7 Hours
Propane (CAS 74-98-6)		
Acute		
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes
LCJU	Modae	
	D .	52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
Propylene Oxide (CAS 75-5	6-9)	
Acute		
Dermal	Rabbit	950 - 1250 mg/kg, 4 Hours
LD50	Nabbr	1.5 ml/kg, 4 Hours
		1.5 mikg, 4 Hours
Inhalation		4197 ppm, 4 Hours
LC50	-	
		4124 mg/m3, 4 Hours
<i>Oral</i> LD50	Rat	382 - 587 mg/kg
	Nat	302 - 307 Highkg
Foluene (CAS 108-88-3) Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg, 24 Hours
Inhalation		
LC50	Mouse	6405 - 7436 ppm, 6 Hours
		5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours
		12.5 - 28.8 mg/l, 4 Hours

1

'n

ļ!

Components	Species	Test Results	
Oral			
LD50	Rat	5000 mg/kg	
* Estimates for product may t	be based on additional con	nponent data not shown.	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitizatio	n		
Respiratory sensitization	Not available.		
Skin sensitization	This product is not expe	ected to cause skin sensitization.	
Germ cell mutagenicity	May cause genetic defe	ects.	
Carcinogenicity	May cause cancer.		
IARC Monographs. Overall	Evaluation of Carcinoge	nicity	
Diethanolamine (CAS 11 Methylene Chloride (CAS Perchloroethylene (CAS Propylene Oxide (CAS 7 Toluene (CAS 108-88-3) OSHA Specifically Regulate	5 75-09-2) 127-18-4) 5-56-9)	2B Possibly carcinogenic to humans. 2B Possibly carcinogenic to humans. 2A Probably carcinogenic to humans. 2B Possibly carcinogenic to humans. 3 Not classifiable as to carcinogenicity to humans. 10.1001-1050)	
Methylene Chloride (CAS		Cancer	
US. National Toxicology Pr		-	
Methylene Chloride (CAS Perchloroethylene (CAS Propylene Oxide (CAS 7	S 127-18-4) Reasonably Anticipated to be a Human Carcinogen.		
Reproductive toxicity	Suspected of damaging	fertility or the unborn child.	
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Respiratory system. Skin. Kidneys. Central nervous system. Eyes. Liver. May cause damage to organs through prolonged or repeated exposure.		
Aspiration hazard	May be fatal if swallowe	ed and enters airways.	
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. May cause damage to organs through prolonged or repeated exposure.		
12. Ecological information	n		

toxicity	Toxic to a	equatic life with long lasting effects.	
Components		Species	Test Results
Diethanolamine (CAS	111-42-2)		
Aquatic			
Algae	IC50	Algae	7.8 mg/L, 72 Hours
Crustacea	EC50	Daphnia	55 mg/L, 48 Hours
Fish	LC50	Fathead minnow (Pimephales promelas)	100 mg/l, 96 hours
Methylene Chloride (C	AS 75-09-2)		
Aquatic			
Algae	IC50	Algae	500.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	1689.5 mg/L, 48 Hours
		Water flea (Daphnia magna)	1250 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	140.8 - 277.8 mg/l, 96 hours
Perchloroethylene (CA	AS 127-18-4)		
Aquatic			
Crustacea	EC50	Daphnia	7.55 mg/L, 48 Hours
		Water flea (Daphnia magna)	6.1 - 9 mg/l, 48 hours

ī

١

i T T

Components		Species	Test Results	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4.82 mg/l, 96 hours	
Propylene Oxide (CAS 75-56	6-9)			
Aquatic				
Crustacea	EC50	Daphnia	350 mg/L, 48 Hours	
Toluene (CAS 108-88-3)				
Aquatic				
Algae	IC50	Algae	433.0001 mg/L, 72 Hours	
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours	
		Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours	
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours	
* Estimates for product may I	be based on	additional component data not shown.		
ersistence and degradability	No data is	available on the degradability of this prod	luct.	
oaccumulative potential	No data a	vailable.		
Partition coefficient n-octa	nol / water (i			
Butane		2.89 -1.43		
Diethanolamine Methylene Chloride		-1.45		
Perchloroethylene		3.4		
Propane	2.36			
Propylene Oxide Toluene	0.03 2.73			
obility in soil	No data a			
ther adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.			
3. Disposal consideratio	•		,	
sposal instructions		d reclaim or dispose in sealed containers	at licensed waste disposal site. Contents	
sposal instructions	under pre sewers/w	ssure. Do not puncture, incinerate or crust ater supplies. Do not contaminate ponds, Dispose of contents/container in accorda		
ocal disposal regulations	•	n accordance with all applicable regulation		
azardous waste code	The waste disposal c		etween the user, the producer and the waste	
US RCRA Hazardous Wast	e U List: Re	ference		
Methylene Chloride (CA Perchloroethylene (CAS Toluene (CAS 108-88-3	127-18-4)	U080 U210 U220		
aste from residues / unused oducts	product re	of in accordance with local regulations. Eme esidues. This material and its container mu instructions).	pty containers or liners may retain some ust be disposed of in a safe manner (see:	
ontaminated packaging	Since em		vaste handling site for recycling or disposal. e, follow label warnings even after container	
4. Transport informatior	ı			
от				

-	/1	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

ΙΑΤΑ

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Labei(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

DOT



Т

IATA; IMDG



Marine pollutant



General information

US federal regulations

IMDG Regulated Marine Pollutant.

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Diethanolamine (CAS 111-42-2)	Listed.
Methylene Chloride (CAS 75-09-2)	Listed.
Perchloroethylene (CAS 127-18-4)	Listed.
Propylene Oxide (CAS 75-56-9)	Listed.
Toluene (CAS 108-88-3)	Listed.
SARA 304 Emergency release notification	
Propylene Oxide (CAS 75-56-9)	100 LBS
OSHA Specifically Regulated Substances (29 CFR	1910.1001-1050)
Methylene Chloride (CAS 75-09-2)	Cancer
	Heart
	Central nen

Heart Central nervous system Liver Skin irritation Eye irritation

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Peactivity Hazard - No
	Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
Propylene Oxide	75-56-9	100	10000 lbs		
SARA 311/312 Hazar chemical	rdous No				
SARA 313 (TRI repoi	rting)				
Chemical name			CAS number	% by wt.	
Methylene Chlori	de		75-09-2	40 - 60	

Product name: Vandalism Mark & Stain Remover

Product #: 1000010459 Version #: 01 Issue date: 02-03-2015

Chemical name	CAS number	% by wt.
Perchloroethylene	127-18-4	10 - 20
Toluene	108-88-3	10 - 20
Diethanolamine Bronylone Oxide	111-42-2	0.1 - 1
Propylene Oxide	75-56-9	0.1 - 1
er federal regulations		
Clean Air Act (CAA) Section 112 Hazardous Air P	ollutants (HAPs) List	
Diethanolamine (CAS 111-42-2)		
Methylene Chloride (CAS 75-09-2) Perchloroethylene (CAS 127-18-4)		
Propylene Oxide (CAS 75-56-9)		
Toluene (CAS 108-88-3)		
Clean Air Act (CAA) Section 112(r) Accidental Re	lease Prevention (40 CFR	68.130)
Butane (CAS 106-97-8)		
Propane (CAS 74-98-6)		
Propylene Oxide (CAS 75-56-9)		
Safe Drinking Water Act Not regulated. (SDWA)		
Drug Enforcement Administration (DEA). Lis Chemical Code Number	t 2, Essential Chemicals (2	21 CFR 1310.02(b) and 1310.04(f)(2) a
Toluene (CAS 108-88-3)	6594	
Drug Enforcement Administration (DEA). Lis		Mixtures (21 CFR 1310.12(c))
Toluene (CAS 108-88-3)	35 %WV	
DEA Exempt Chemical Mixtures Code Number		
Toluene (CAS 108-88-3)	594	
state regulations		
US. Massachusetts RTK - Substance List		
Butane (CAS 106-97-8)		
Diethanolamine (CAS 111-42-2) Methylene Chloride (CAS 75-09-2)		
Perchloroethylene (CAS 127-18-4)		
Propane (CAS 74-98-6)		
Propylene Oxide (CAS 75-56-9)		
Toluene (CAS 108-88-3)		
US. New Jersey Worker and Community Right-to	-Know Act	
Butane (CAS 106-97-8)		
Diethanolamine (CAS 111-42-2) Mathylana Chlorida (CAS 75-09-2)		
Methylene Chloride (CAS 75-09-2) Perchloroethylene (CAS 127-18-4)		
Propane (CAS 74-98-6)		
Propylene Oxide (CAS 75-56-9)		
Toluene (CAS 108-88-3)		
US. Pennsylvania Worker and Community Right-	to-Know Law	
Butane (CAS 106-97-8)		
Diethanolamine (CAS 111-42-2)		
Methylene Chloride (CAS 75-09-2) Perchloroethylene (CAS 127-18-4)		
Propane (CAS 74-98-6)		
Propylene Oxide (CAS 75-56-9)		
Toluene (CAS 108-88-3)		
US. Rhode Island RTK		
Butane (CAS 106-97-8)		
Diethanolamine (CAS 111-42-2)		
Methylene Chloride (CAS 75-09-2)		
Perchloroethylene (CAS 127-18-4) Propane (CAS 74-98-6)		
Propylene Oxide (CAS 75-56-9)		
Toluene (CAS 108-88-3)		

i

ļ|

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

	Cocoyl Diethanolamide (CAS 68603-42-9)	Listed: June 22, 2012
	Diethanolamine (CAS 111-42-2)	Listed: June 22, 2012
	Methylene Chloride (CAS 75-09-2)	Listed: April 1, 1988
	Perchloroethylene (CAS 127-18-4)	Listed: April 1, 1988
	Propylene Oxide (CAS 75-56-9)	Listed: October 1, 1988
	US - California Proposition 65 - CRT: Listed date/	Developmental toxin
	Toluene (CAS 108-88-3)	Listed: January 1, 1991
	US - California Proposition 65 - CRT: Listed date/	Female reproductive toxin
	Toluene (CAS 108-88-3)	Listed: August 7, 2009
Intern	ational Inventories	

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	02-03-2015
Version #	01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

.