

MATERIAL SAFETY DATA SHEET
FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20)

DATE OF PREP: 6-01-01 Supersedes 6/10/97
GPW

NPCA HMIS

H = 1

F = 4

R = 0

SECTION I

MANUFACTURED FOR: R.C. Musson Rubber Company

STREET ADDRESS: 1320 East Archwood **CITY, STATE, AND ZIP CODE:** Akron, OH 44306

EMERGENCY TELEPHONE: 1-800-228-4583 8AM-5PM Eastern, Chemtrec 1-800-424-9300 (24 hours)

PRODUCT CLASS: Flammable Contact Adhesive **TRADE NAME:** Neoprene Contact Adhesive

MANUFACTURER'S CODE IDENTIFICATION: No. 400

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	NTP, IARC/ OSHA CARC	PERCENT	PEL (OSHA) PPM TWA	VAPOR PRESSURE
Flammable Solvents				
Hexane Cas # 110-54-3	No	43.2%	50 -	125 mm HG @ 68° F
MEK Cas # 78-93-3	No	19.6%	200 -	49.5 mm HG @ 68 °F
Toluene Cas # 108-88-3	No	15.7%	100 -	22 mm HG @ 68° F

SECTION III - PHYSICAL DATA

BOILING RANGE: 149 Deg. TO 231 Deg. F **VAPOR DENSITY:** HEAVIER LIGHTER THAN AIR

EVAPORATION RATE: FASTER SLOWER THAN ETHER

PERCENT VOLATILE BY VOLUME: 79.81% **WEIGHT PER GAL:** 7.0 - 7.5 lbs.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY: Flammable Liquid **FLASH POINT:** 10° F **LEL.:** 1.0%

EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS: DO NOT STORE OR MIX WITH STRONG OXIDANTS LIKE CHLORINE OR CONCENTRATED OXYGEN.

SPECIAL FIRE FIGHTING PROCEDURES: USE AIR SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED AREAS. COOL EXPOSED CONTAINER WITH WATER SPRAY. AVOID BREATHING VAPOR OR FUMES.

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE: CAUSES DRYING OF SKIN AND SEVERE EYE IRRITATION. BREATHING OF VAPORS CAUSES HEADACHES, DIZZINESS, NAUSEA, VOMITING, AND LOSS OF CONSCIOUSNESS.

CALIFORNIA PROPOSITION 65: THE STATE OF CALIFORNIA RECOGNIZES THAT TOLUENE AND HEXANE CONTAINS A SUBSTANCE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

EMERGENCY AND FIRST AID PROCEDURES: SKIN CONTACT - WASH EXPOSED AREA WITH SOAP OR WATER. EYE CONTACT - FLUSH EYES WITH PLENTY OF WATER FOR 15 MINUTES OR UNTIL IRRITATION SUBSIDES. SEEK MEDICAL ATTENTION. IF INHALED - REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. GIVE OXYGEN IF BREATHING IS DIFFICULT. CALL A PHYSICIAN.

SECTION VI - REACTIVITY DATA

STABILITY: UNSTABLE STABLE

CONDITIONS TO AVOID: HEAT AND FIRES.

INCOMPATIBILITY: (MATERIALS TO AVOID) STRONG OXIDANTS: LIQUID CHLORINE, OXYGEN, NA AND K HYPOCHLORITE.

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE AND DIOXIDE, FUMES, BLACK SMOKE.

HAZARDOUS POLYMERIZATION: MAY OCCUR WILL NOT OCCUR

CONDITIONS TO AVOID: NONE KNOWN

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: KEEP PEOPLE CLEAR OF AREA. RECOVER FREE LIQUID. ADD ABSORBENTS (SAND, SAWDUST, EARTH, ETC.) TO SPILL AREA. AVOID BREATHING VAPORS. VENTILATE CONFINED AREAS. OPEN WINDOWS AND DOORS. KEEP FROM SPILLWAYS AND DRAINS.

WASTE DISPOSAL METHOD: ASSURE CONFORMITY WITH APPLICABLE DISPOSAL REGULATIONS. DISPOSE ONLY AT APPROVED DISPOSAL SITES. CAN BE INCINERATED IN A FURNACE.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: AIR SUPPLIES MASKS FOR CONCENTRATIONS ABOVE 200 PPM.

VENTILATION: LOCAL EXHAUST-FACE VELOCITY 60 FPM, USE EXPLOSION-PROOF ELECTRICAL EQUIPMENT. NO SMOKING OR OPEN LIGHTS. USE ONLY WITH ADEQUATE VENTILATION.

PROTECTIVE GLOVES: PLASTIC GLOVES TO PREVENT PROLONGED EXPOSURE.

EYE PROTECTION: SAFETY GLASSES OR GOGGLES.

OTHER PROTECTIVE EQUIPMENT: LONG-SLEEVED CLOTHING OR RUBBER APRONS.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: FLAMMABLE. BREATHING OF VAPORS MAY BE HARMFUL. CAUSES EYE INJURY AND SKIN IRRITATION.

OTHER PRECAUTIONS: KEEP FROM FIRES, SPARKS, AND HEAT. DO NOT LEAVE CONTAINER OPEN. AVOID CONTACT WITH EYES OR SKIN. FOR PROFESSIONAL USE ONLY.